



Junction Boxes for Self-Regulating Heating Cables (3 and More Circuits)

Application

Junction boxes for 3 and more self-regulating heating cables connection are designed for connecting of self-regulating electrical heating cables to the power

network* and for the branching of self-regulating heating cables. The box also supports branching of the power cable in utility networks.

For installation onto a wall, onto a nearby metal structure or using a bracket directly onto the pipeline (brackets supplied separately).



The junction boxes are compatible with all types of self-regulating heating cables.

- 1. Power cable
- 2. Junction box
- 3. Heating cable

- 4. Mechanical cable protection
- 5. Cable entry unit

- 1. Power cable
- 2. Junction box
- 3. Heating cable

- 4. Mechanical cable protection
- 5. Cable entry unit

Power Supply of Self-Regulating Heating Cables

Technical Data

Dust and moisture protection rating	IP66
Explosion protection marking	Ex eb IIC T6...T3 Gb Ex tb IIIC T85°C... T165°C Db
Temperature group of the explosion hazard area	T6
Operating ambient temperature range	-60...+55 °C
Operating voltage	max 550 V
Operating current	max 50 A
Enclosure dimensions	160×160×94.5 mm
Total weight (maximum)	2.76 kg
Material Box / Color	Glass fiber reinforced polyester / Black

Approval



CETS 23 ATEX 029X
II 2G Ex eb IIC T6...T3 Gb
II 2D Ex tb IIIC T85°C...T165°C Db



Accessories (to be ordered separately)

Connection kit for self-regulating heating cables is specified depending on the type of cable used.



Brackets PB, KP, PL.JB0606 – for mounting the box onto the pipeline.

Z-profile – for mounting the box onto a metal structure or onto a wall.

Metal pipe strap PFS/3 – for mounting the bracket onto the pipeline.

Cable entry unit LEK/U – for penetrating of thermal insulation.

Construction



Quantity, type of terminals and placement of DIN-rail with terminal block could differ from drawings.

PREMIUM

Delivery Set

Model	Cable glands and plugs (P=plastic; B=brass)								Earthing tag	Terminated earthing wire	Pipe installation support	Terminal block	Type of terminals	Order code
	C A B D													
	Side A		Side B		Side C		Side D							
	Cable gland	Screw plug	Cable gland	Screw plug	Cable gland	Screw plug	Cable gland	Screw plug						
JB2221-333-1X11					1xM25 B			3xM25 P	V	V	V	3L, 2N, 2PE/ 6L, 3N, 3PE	screw/ spring	3210102100
JB2221-333-1X12					1xM25 B		1xM25 B	2xM25 P	V	V	V			3210102101
JB2221-333-1X13					1xM25 B		1xM25 P	2xM25 P	V	V	V			3210102102
JB2221-333-1X14					1xM25 B		2xM25 B	1xM25 P	V	V	V			3210102103
JB2221-333-1X15					1xM25 B		2xM25 P	1xM25 P	V	V	V			3210102104
JB2221-333-1X16					1xM25 P			3xM25 P	V	V	V			3210102105
JB2221-333-1X17					1xM25 P		1xM25 P	2xM25 P	V	V	V			3210102106
JB2221-333-1X18					1xM25 P		2xM25 P	1xM25 P	V	V	V			3210102107
JB2221-333-1X19					1xM25 B		1xM25 P 1xM25 B	1xM25 P	V	V	V			3210102108
JB2221-333-2X11				1xM25 P	1xM25 B	1xM25 P	1xM25 P	1xM25 P	V	V				3210102109
JB2221-333-2X12				1xM25 P	1xM25 B	1xM25 P	1xM25 B	1xM25 P	V	V				3210102110
JB2221-333-2X13				1xM25 P	1xM25 B	1xM25 P	2xM25 B		V	V				3210102111
JB2221-333-2X14				1xM25 P	1xM25 B	1xM25 P	2xM25 P		V	V				3210102112
JB2221-333-2X15				1xM25 P	2xM25 B		2xM25 B		V	V				3210102113
JB2221-333-2X16				1xM25 P	1xM25 B 1xM25 P		2xM25 P		V	V				3210102114
JB2221-333-2X17				1xM25 P	1xM25 P	1xM25 P	1xM25 P	1xM25 P	V	V				3210102115
JB2221-333-2X18				1xM25 P	1xM25 P	1xM25 P	2xM25 P		V	V				3210102116
JB2221-333-2X19				1xM25 P	2xM25 P		2xM25 P		V	V				3210102117
JB2221-333-2X20				1xM25 P	2xM25 B		1xM25 P	1xM25 P	V	V				3210102118
JB2221-333-2X21				1xM25 P	1xM25 B 1xM25 P		1xM25 B 1xM25 P		V	V				3210102119
JB2221-333-2X22			1xM25 P		1xM25 B 1xM25 P		1xM25 B 1xM25 P		V	V				3210102120
JB2221-333-2X23			1xM25 P		2xM25 P		2xM25 P		V	V				3210102121

Order codes are valid for junction boxes with push-in terminal block. Additional junction box configurations are available upon request.

° X = 1 for screw type terminal block; X=2 for push-in type terminal block